

DA 2628

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



- Customised kitchen design – fully integrated in 1180 mm width
- Unique user convenience – Con@ctivity
- Powerful – 640 m³/h on the booster setting
- Energy-efficient and quiet – powerful ECO motor
- Elegant and efficient – edge extraction panels

A⁺

EAN: 4002516001515 / Material number: 10851370 / Old Material Number: 28262855GB

Construction type	
Integrated extractor	•
Operating modes	
Type of air guide	air extraction
Design	
Colour	Stainless steel
Edge extraction	•
User convenience	
Miele@home	•
Automatic function Con@ctivity 3.0 (WiFi)	•
Electronic controls	•
Power levels (number without Booster level)	3
Miele@mobile app	•
Programmable Booster level switch-off	•
Run-on time 5/15 min.	•
Grease filter saturation indicator	•
Grease filter saturation indicator programmable	•
Efficiency and sustainability	
Energy efficiency class (A+++ to D)	A+
Annual energy consumption in kWh/year	26.8
Fluid dynamic efficiency class	A
Lighting efficiency class	A
Grease filtering efficiency class	A
ECO motor	•
PowerManagement system	•
Cleaning convenience	
Easy-to-clean canopy interior – CleanCover	•
Filter system	
Number of dishwasher-safe stainless steel grease filters (10-ply)	4
Lighting	
LED	•
Number x W	3 x 4,5 W
Light intensity in lx	700 lx
Colour temperature in K	3500 Kelvin
Dimmer function	•
Blower	
Dual-action fan	•
DC motor	•
Extraction	
Air throughput in Level 1 (m ³ /h) according to EN 61591	200
Air throughput in Level 2 (m ³ /h) according to EN 61591	300
Air throughput in Level 3 (m ³ /h) according to EN 61591	400
Air throughput in Booster level (m ³ /h) according to EN 61591	640
Sound power in Level 1 (dB(A) re 1 pW) according to EN 60704-3	36.0
Sound power in Booster level (dB(A) re 1 pW) acc. to EN 60704-3	62.0
Sound power in Level 2 (dB(A) re 1 pW) according to EN 60704-3	44.0

DA 2628

Extractor unit

with energy-efficient LED lighting and light-touch switches for easy use.



EAN: 4002516001515 / Material number: 10851370 / Old Material Number: 28262855GB

Sound power in Level 3 (dB(A) re 1 pW) according to EN 60704-3	51.0
Noise pressure level in Intensive level (dB(A) re 20 µPa) according to EN 60704-2-13	48.0
Sound pressure in Level 1 (dB(A) re 20 µPa) according to EN 60704-2-13	22.0
Sound pressure in Level 2 (dB(A) re 20 µPa) according to EN 60704-2-13	30.0
Sound pressure in Level 3 (dB(A) re 20 µPa) according to EN 60704-2-13	37.0
Safety	
Safety switch-off	•
Technical data	
Canopy width in mm	1180
Canopy height in mm	63
Canopy depth in mm	293
Minimum height above electric hobs in mm	450
Minimum height above gas hobs (max. 12.6 kW total power, burner ≤ 4.5 kW) in mm	650
Net weight in kg	15.0
Length of supply lead in m	1.5
Standard plug fitted	•
Total rated load in kW	0.09
Voltage in V	230
Fuse rating in A	10
Number of phases	1
Frequency in Hz	50
Installation notes	
Extraction ducting connection at top	•
Extraction connection at top and rear	•
Diameter of exhaust duct in mm	150
Combination with WiFi-enabled Miele hob	recommended
Optional accessories	
Active charcoal filter	Nein